

## PB/ICTD/Q/20254/01 SUPPLY AND DELIVERY OF IT EQUIPMENT AND ACCESSORIES FOR AUDIO VIDEO BROADCASTING AND LIVE STREAMING POLITEKNIK BRUNEI, NEGARA BRUNEI DARUSSALAM

| ITEM | BANYAK    | KETERANGAN  |
|------|-----------|---|
| ITEM | QUANTITY  | DESCRIPTION   |
| 1    | 1-2 Units | 4K PTZ Camera   |
|      |           | - Processor : DIGIC DV6 Processor                       |
|      |           | - Optical Zoom : 20x optical zoom                       |
|      |           | - Digital Zoom : 20x optical zoom                       |
|      |           | - Communication Control : LAN, Wi-Fi, Serial, IR        |
|      |           | - Network Terminal : LAN x 1, RJ45, 1000Base-T          |
|      |           | - HDMI Out Terminal : HDMI connector                    |
|      |           | - RS-422 Terminal : RJ45 connector                      |
|      |           | - USB Terminal : Type-A (USB 2.0), Type-C (USB 3.0)     |
|      |           |   |
| 2    | 1-2 Units | Heavy-Duty Tripod Stand with Mounting for 4K PTZ Camera |
|      |           | (Must be compatible with Item 1)                        |
|      |           | - Minimum Height: 78 cm                                 |
|      |           | - Payload Weight: ± 40 kg                               |
| _    |           |   |
| 3    | 1-2 Sets  | Mirrorless Camera                                       |
|      |           | - 33MP Full-Frame Exmor R CMOS Sensor                   |
|      |           | - 4K 60p Video in 10-Bit, S-Cinetone                    |
|      |           | - Up to 10 fos shooting, ISO 100-51200                  |
|      |           | - 3" Touchscreen LCD                                    |
|      |           | - Extra Battery (2 units)                               |
|      |           | - Include Memory Card 128GB class 10 (2 units)          |
|      |           | - Include carry bag (2 units)                           |
|      |           |   |
| 4    | 1-2 Units | FE 24-70mm f/2.8 GM II Lens                             |
|      |           | (Must be compatible with Item 3)                        |
|      |           | - Full-Frame f/2.8 to f/22                              |
|      |           | - Four XD Linear AF Motors, Floating Focus              |
|      |           | - Nano AR Coating II and Fluorine Coating               |
| _    |           |   |
| 5    | 1-2 Units | Wireless HDMI Video Transmitter and Receiver            |
|      |           | - DC Input, Battery or USB power support                |
|      |           | - Minimum 1080p60 SDI or HDMI Transmission              |
|      |           | - Less Latency  |
|      |           | - Select channel with least interference                |
|      |           | - Dual-Channel Transmission                             |
|      |           | - Wi-Fi: Yes  |
|      |           | - Video Input: Transmitter and Receiver :               |
|      |           | 1 x HDMI Type A Input, 1 x BNC Input                    |
|      |           | - Video Output: Transmitter and Receiver :              |
|      |           | 1 x HDMI Type A Output, 1 x BNC Output                  |
|      | 4.6.1. 11 | Mindon Internation Contract                             |
| 6    | 1-6 Units | Wireless Intercom System                                |
|      |           | - Full-Duplex, Use Any Headset as Master                |
|      |           | - True Wireless Headset, No Bodypack                    |
|      |           | - Al Audio Echo Cancellation (AEC) 2.0                  |
|      |           | - Expandable to 13 Headsets                             |
|      |           | - 24-Hour Battery Life, 3.5mm Monitor Jack              |
|      |           | - Rechargeable Batteries, Charging Station              |

| 7        | 1-4 Units            | Heavy Duty USB Extension Cable   |
|----------|----------------------|--|
| <u> </u> |                      | - with USB signal repeater booster   |
|          |                      | - Minimum 20 meters  |
|          |                      | - Male to Female   |
|          |                      |  |
| 8        | 1-2 Units            | Wireless Microphone System   |
|          |                      | - 2 x Clip-On transmitter/recorder mics  |
|          |                      | - 32-Bit float internal recording  |
|          |                      | - Intelligent Noise Cancelling   |
|          |                      | - Built-In rechargeable batteries  |
|          |                      | - Connects to Computers, Cameras, iOS/Android Devices  |
|          |                      | - Records 14 hours of audio or higher  |
|          |                      | - Bright OLED Display, Headphone Out   |
|          |                      | - 820ft Wireless Range or higher   |
|          |                      |  |
| 9        | 1-3 Units            | Power Bank   |
|          |                      | - Minimum 20,000 mAh   |
| 10       | 4.11                 | Distribution / December  |
| 10       | 1 Unit               | Digital Mixer / Recorder   |
|          |                      | - Portable Podcasting/Music Studio - 10 Faders to Control Audio Levels   |
|          |                      | - Mix-Minus Prevents Call Echo & Feedback  |
|          |                      | - 4 Headphone Outputs for Host and Guests  |
|          |                      | - 6 XLR-1/4" Mic/Line Inputs with +48V   |
|          |                      | - Multitrack Recording via SD Card and USB   |
|          |                      | - Built-In Effects and 3-Band EQ   |
|          |                      | - DC Input, Battery or USB power support   |
|          |                      | De impac, buttery or osb power support   |
|          |                      |  |
| 11       | 1-2 Units            | Tripod Stand   |
| 11       | 1-2 Units            | Tripod Stand - Load Capacity: 2kg - 8kg  |
| 11       | 1-2 Units            |  |
| 11       | 1-2 Units            | - Load Capacity : 2kg - 8kg  |
| 11       | 1-2 Units            | - Load Capacity : 2kg - 8kg<br>- Max Height : 59.1"  |
| 11       | 1-2 Units            | - Load Capacity : 2kg - 8kg - Max Height : 59.1" - Minimum Height : 15.8"  |
| 11       | 1-2 Units            | - Load Capacity : 2kg - 8kg - Max Height : 59.1" - Minimum Height : 15.8" - Folded Length : 15.7"  |
|          |                      | - Load Capacity: 2kg - 8kg - Max Height: 59.1" - Minimum Height: 15.8" - Folded Length: 15.7" - Leg Sections: 4 - 494 Ball Head with Pan & Friction Knobs  |
| 11       | 1-2 Units            | - Load Capacity: 2kg - 8kg - Max Height: 59.1" - Minimum Height: 15.8" - Folded Length: 15.7" - Leg Sections: 4 - 494 Ball Head with Pan & Friction Knobs  |
|          |                      | - Load Capacity: 2kg - 8kg - Max Height: 59.1" - Minimum Height: 15.8" - Folded Length: 15.7" - Leg Sections: 4 - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord - Surge Protector  |
|          |                      | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters   |
|          |                      | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  |
|          |                      | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters   |
|          | 1-3 Units            | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  - Minimum 2 USB Charging ports  |
| 12       |                      | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  |
| 12       | 1-3 Units            | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera  |
| 12       | 1-3 Units            | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera  - Wireless Camera Control via Bluetooth  - Horizontal & Vertical Modes  |
| 12       | 1-3 Units            | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera  - Wireless Camera Control via Bluetooth   |
| 12       | 1-3 Units            | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera  - Wireless Camera Control via Bluetooth  - Horizontal & Vertical Modes  - 2450mAh Battery, 10-Hour Runtime or Higher  |
| 12       | 1-3 Units            | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera  - Wireless Camera Control via Bluetooth  - Horizontal & Vertical Modes  - 2450mAh Battery, 10-Hour Runtime or Higher  - Lightweight Design, up to 1.9kg Payload   |
| 12       | 1-3 Units            | - Load Capacity: 2kg - 8kg - Max Height: 59.1" - Minimum Height: 15.8" - Folded Length: 15.7" - Leg Sections: 4 - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord - Surge Protector - Length: Minimum 10 meters - No. of Socket: Minimum 6 socket plugs - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera - Wireless Camera Control via Bluetooth - Horizontal & Vertical Modes - 2450mAh Battery, 10-Hour Runtime or Higher - Lightweight Design, up to 1.9kg Payload - 1.4" Full Color Touchscreen - Includes Extended Grip/Tripod  |
| 12       | 1-3 Units            | - Load Capacity: 2kg - 8kg - Max Height: 59.1" - Minimum Height: 15.8" - Folded Length: 15.7" - Leg Sections: 4 - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord - Surge Protector - Length: Minimum 10 meters - No. of Socket: Minimum 6 socket plugs - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera - Wireless Camera Control via Bluetooth - Horizontal & Vertical Modes - 2450mAh Battery, 10-Hour Runtime or Higher - Lightweight Design, up to 1.9kg Payload - 1.4" Full Color Touchscreen - Includes Extended Grip/Tripod  |
| 12       | 1-3 Units  1-2 Units | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera  - Wireless Camera Control via Bluetooth  - Horizontal & Vertical Modes  - 2450mAh Battery, 10-Hour Runtime or Higher  - Lightweight Design, up to 1.9kg Payload  - 1.4" Full Color Touchscreen  - Includes Extended Grip/Tripod  Headphones  - Type: Closed-back dynamic                            |
| 12       | 1-3 Units  1-2 Units | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera  - Wireless Camera Control via Bluetooth  - Horizontal & Vertical Modes  - 2450mAh Battery, 10-Hour Runtime or Higher  - Lightweight Design, up to 1.9kg Payload  - 1.4" Full Color Touchscreen  - Includes Extended Grip/Tripod  Headphones  - Type: Closed-back dynamic  - Diameter: 45mm or above |
| 12       | 1-3 Units  1-2 Units | - Load Capacity: 2kg - 8kg  - Max Height: 59.1"  - Minimum Height: 15.8"  - Folded Length: 15.7"  - Leg Sections: 4  - 494 Ball Head with Pan & Friction Knobs  Power Extension Cord  - Surge Protector  - Length: Minimum 10 meters  - No. of Socket: Minimum 6 socket plugs  - Minimum 2 USB Charging ports  Gimbal Stabilizer for Camera  - Wireless Camera Control via Bluetooth  - Horizontal & Vertical Modes  - 2450mAh Battery, 10-Hour Runtime or Higher  - Lightweight Design, up to 1.9kg Payload  - 1.4" Full Color Touchscreen  - Includes Extended Grip/Tripod  Headphones  - Type: Closed-back dynamic                            |

| 15 | 1 Unit | Cardioid Condenser Microphone                        |
|----|--------|--|
|    |        | - Cardioid Pattern Lessens Room Noise                |
|    |        | - Extended Frequency Response                        |
|    |        | - Must include tripod stand for Microphone           |
|    |        | - Pivoting Stand Mount (include mounting for tripod) |
|    |        |  |
| 16 | 1 Unit | XLR Cable  |
|    |        | - Male-to-male connection                            |
|    |        | - Length : Minimum 50 meters                         |
|    |        |  |

## Further Requirements:

• Warranty to be included where applicable

## Note:

If you are interested in submitting an offer, you are required to make a payment of BND\$5.00 to Finance Division on the 12th floor, Politeknik Brunei.

You are also required to fill in the online PARTICIPATION FORM at <a href="https://bit.ly/3Hp2RLt">https://bit.ly/3Hp2RLt</a> and upload the payment receipt into the form. Quotation Form (RFQ) and related documents will be sent via email.

If you require further information, please do not hesitate to contact <a href="mailto:itd@pb.edu.bn">itd@pb.edu.bn</a> or contact no+673-2234466 ext 313 / 218.

Thank you and looking forward to your participation.